

## Pojistné ventily pro zásobníky TV

Maximální kapacita 2200 l/h při  $\Delta P$  100 kPa



Dimenze	Otevírací tlak $P_O$	Pojistný výkon kW	Balení	Objednací č.	Kč/ks
CU 15 mm (1/2") DN 15	6 bar	75	25	6915B.60PE	598,-
CU 15 mm (1/2") DN 15	8 bar	75	25	6915B.80PE	598,-
CU 15 mm (1/2") DN 15	10 bar	75	25	6915B.100PE	598,-



### Hadice pro napojení do sifonu

Dimenze	Objednací č.	Kč/m
DN 15	69S	51,-



Cu 22 mm DN 20	6 bar	150	1	6920B.60PE	2 353,-
Cu 22 mm DN 20	8 bar	150	1	6920B.80PE	2 353,-
Cu 22 mm DN 20	10 bar	150	1	6920B.100PE	2 353,-




Maximální kapacita 6200 l/h při  $\Delta P$  100 kPa

1" DN 20	6 bar	150	1	6925B.60	2 353,-
1" DN 20	8 bar	150	1	6925B.80	2 353,-
1" DN 20	10 bar	150	1	6925B.100	2 353,-

## Pojistné skupiny pro zásobníky TV

Maximální kapacita 2500 l/h při  $\Delta P$  100 kPa



Dimenze	Otevírací tlak $P_O$	Pojistný výkon kW	Balení	Objednací č.	Kč/ks
3/4" DN 20	6 bar	150	1	6920VR.60B	1 396,-
3/4" DN 20	8 bar	150	1	6920VR.80B	1 396,-
3/4" DN 20	10 bar	150	1	6920VR.100B	1 396,-

